

# CROSSMAX SLR DISC 12



**Use:** use only on a Cross-country or Cross-mountain MTB fitted with disc brakes. Any other use (such as on a tandem, road bike, cyclo-cross bike, free-ride or downhill bike...) is highly inadvisable, is the sole responsibility of the user and voids the Mavic warranty.

Recommended maximum weight of the cyclist and equipment: 85 kg.

## WHEEL WEIGHT WITHOUT QUICK-RELEASE SKEWER

Front: 660 g  
Rear: 780 g

## WHEEL REFERENCES

Front: 127 754 10  
Rear: 127 755 13  
Pair: 127 756 14

RIMS	SALES REFERENCES
	Front: 308 613 10 Rear: 308 613 13
	<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p><b>Ø VALVE HOLE</b> Ø: 6.5 mm Length: ≥ 32 mm</p> </div> <div style="width: 45%;"> <p><b>RECOMMENDED TYRE WIDTH</b> Dimensions: Ø 26" ETRTO 559 x 19C compatible and Tubeless UST. Recommended tyre width: 1.5" to 2.3"</p> </div> </div> <p><b>When replacing the front rim:</b></p> <ol style="list-style-type: none"> <li>With the valve hole near you, the raised indicator bump must be to the <b>right</b> of the valve hole.</li> <li>The spoke in the first hole to the right of the valve hole is a non-braking spoke and should be introduced into the disc side.</li> </ol> <p><b>When replacing the rear rim:</b></p> <ol style="list-style-type: none"> <li>With the valve hole near you, the two raised indicator bumps must be to the <b>right</b> of the valve hole.</li> <li>The spoke in the first hole to the right of the valve hole should be introduced into the drive side in a marked hole on the hub.</li> </ol>

HUBS	MAINTENANCE: Clean with a dry cloth or soapy water if necessary. Do not use a high-pressure washer.

WHEEL BUILDING	REFERENCES AND LENGTHS
	Front and rear non-drive side: 308 642 01, length 269 mm (per 10 + 1 decorated, integrated nipples) Rear drive side: 308 641 01, length 239 mm (per 10, integrated nipples)
<b>FEATURES:</b>	<b>LACING PATTERN:</b>
Black swaged, straight pull Zicral spokes (with one decorated per wheel, disc side) with integrated, self-locking M7 aluminum spoke nipples	Front: 2-cross lacing on both sides Rear: Isopulse
	<b>TENSION:</b>
	Front disc side: 110 to 135 kg Rear drive side: 115 to 145 kg

ACCESSORIES	WHEELS SUPPLIED WITH:	MAINTENANCE
<ul style="list-style-type: none"> <li>• BX 601 front quick-release M40140</li> <li>• BX 601 rear quick-release M40141</li> <li>• 2 Removable round UST valves 129 838 01</li> <li>• 2 Mavic wheel bags 857 144 01</li> <li>• Axle reducers 15=&gt;9 mm 996 941 01 (mounted on front wheel)</li> <li>• Adapters 12x142 mm 308 593 01 (with rear wheel)</li> <li>• Axle reducers 12=&gt;9.5 mm 308 731 01 (mounted on rear wheel)</li> <li>• Computer magnet M40540 (with front wheel)</li> <li>• 2 multifunction adjustment wrenches 325 423 01</li> <li>• Chain disc 308 755 01 (mounted on rear wheel)</li> <li>• 2 sets of specific disc screws (6 screws per set) 308 719 01</li> <li>• User guides</li> </ul>		Front hub assembly diameter conversion Replacing the front axle and bearings Replacing the rear axle and bearings Maintaining and replacing the free wheel mechanism Replacing a spoke Replacing the front rim Replacing the rear rim
		See 2009 TM, page 25 See 2003 TM, page 18 See 2012 TM, page 20 See 2009 TM, page 29 See 2003 TM, page 24 See 2009 TM, page 37 See 2006 TM, page 17
		Refer to the website for quick and convenient access to information: <a href="http://www.tech-mavic.com">www.tech-mavic.com</a>